



# ZEBRA DS9808-R

## NEXT-GENERATION HYBRID PRESENTATION IMAGER WITH INTEGRATED RFID

### DEPLOY THE BEST OF ALL WORLDS FOR A TRULY FUTURE-PROOF AND COST-EFFECTIVE POS.

Zebra's DS9808-R is the first combination 1D/2D bar code scanner and RFID reader and the first combination handheld/hands-free UHF RFID reader. Its revolutionary imaging engine enables the capture of 1D and 2D bar codes as well as images and signatures, with record swipe speeds on both 1D and 2D bar codes. In addition, the read range for RFID tags can be adjusted to suit the environment. For example, the RFID read range in presentation mode can be decreased to prevent inadvertent reading of RFID tags in a nearby cash-wrap, while the range in handheld (triggered) mode can be increased to read RFID tags that are further away. The DS9808-R offers the flexibility to accommodate virtually any type of data capture application, including support for: 1D and 2D paper and mobile bar codes, mobile coupons, mobile loyalty cards, mobile boarding passes, PDF417 bar codes, reading/writing\* RFID tags

### REALIZE THE BENEFITS OF ITEM-LEVEL RFID WITH THE LAST LINK IN THE RFID CHAIN

The DS9808-R complements Zebra's RFID portfolio, allowing retailers to implement RFID from the receiving dock to the POS. Retailers can realize the benefits of real-time item-level inventory visibility, including: timely re-ordering to eliminate out-of-stocks and associated lost sales, increased inventory turns and reduced inventory carrying costs, real-time trending analysis for better purchasing decisions, timely replenishment of your shelves with minimal human intervention.

### RICH BEST-IN-CLASS RFID FUNCTIONALITY AT THE POS

The comprehensive RFID feature set enables retailers to maximize the value of RFID technology in the store. In addition to reading tags to complete purchases, capabilities include: Commission tags on new inventory items and returned goods. Built-in filtering prevents accidental multiple entries of the same tag - Associates will hear a single beep as the tag data is captured and entered into the transaction, just as if a bar code was scanned, providing associates with a familiar and intuitive process that eliminates the need for training. Special RFID data conversion software for on-the-fly translation of the RFID EPC tag data to UPC bar code data. A pilot test or full RFID solution can be implemented quickly, easily and cost-effectively into any existing retail technology environment.

### MAXIMUM EASE OF USE FOR MAXIMUM THROUGHPUT

The DS9808-R allows associates to instantly switch scanning modes. Switching from hands-free presentation style scanning to handheld mode is as easy as picking up the device. The unique tri-function trigger design enables retailers to assign up to three specific functionalities in the same trigger. For example, the upper and lower triggers could activate the bar code reader and pressing both triggers together could activate the RFID reader.

### MULTIPLE FUNCTIONS ON A SINGLE DEVICE OFFERS RAPID RETURN ON INVESTMENT (ROI)

With the flexible DS9808-R, there is no need to purchase multiple devices to support different types of data capture in your enterprise. The DS9808-R provides the functionality of an RFID reader/writer, an image capture device and a bar code scanner all in a single device. Capital and operational costs are significantly reduced, there are fewer devices to purchase and manage.

### FEATURES

#### Innovative hybrid design

Truly designed for ease of use for both hands-free and handheld scanning; dynamically switches between modes

#### Multiple technologies, one device

The DS9808-R supports several technologies eliminating the need to purchase and maintain multiple devices. A single device supports a wide range of data capture applications including reading and writing\* of RFID tags, decoding 1D, 2D and PDF417 symbologies and capturing images.

#### Omni-directional bar code scanning; wide working range, laser aiming pattern

Easy to use; no need to align item and scanner; virtually no training require

#### Withstands multiple 4 ft./1.2 m drops to concrete

Designed to endure the rigors of everyday use for maximum reliability, uptime and a low total cost of ownership

#### Swipe speed programmable up to 100 inches/254 cm per second

Optimized scanning speed delivers robust performance and accurate capture of a wide variety of bar codes

#### Maximum flexibility and control

\*Tag “write” commands are supported via USB only.

For more information on the DS9808-R hybrid presentation imager, please visit us on the web at [www.zebra.com/ds9808-R](http://www.zebra.com/ds9808-R) or access our global contact directory at [www.zebra.com/contact](http://www.zebra.com/contact)

Independent RFID antenna power level controls for both hands-free and handheld operation help avoid inadvertent RFID tag reads; triggered operation in handheld mode offers unmatched control for reading RFID tags at the POS

## SPECIFICATIONS CHART

| PHYSICAL CHARACTERISTIC             |   | PERFORMANCE CHARACTERISTICS                                      |  |
|-------------------------------------|---|--|--|
| Dimensions                          | 8.5 in. (max) H x 3.5 in. W x 6 in. D<br>21.6 cm (max) H x 8.9 cm W x 15.2 cm D   | <i>DS9808SR, DS9808LR, DS9808DL** and DS9808LL** Imager Mode</i> |  |
| Weight                              | 16.4 oz/465 g   | Light Source   | Aiming Pattern: 650nm laser diode<br>Illumination: 630nm LED   |
| Voltage and Current                 | Nominal: 5V ±5% VDC @ 1.2 A   | Imager Field of View   | 39° H x 25° V  |
| Data Capture Options                | 1D/2D bar codes and RFID tags   | Roll/Pitch/Yaw   | 360°, ±65°, ±60°   |
| Color                               | Twilight Black  | Swipe Speed  | Programmable up to 100 in./254 cm per second (Horizontal Read Rate)  |
| <b>SYMBOLGY DECODE CAPABILITY</b>   |   | Frame Rate   | Up to 60 frames per second   |
| 1D                                  | UPC/EAN, Code 11, Code 39, Code 128, Code 93, Codabar/NW7, MSI Plessey, I 2 of 5, Korean 3 of 5, GS1 DataBar, Base 32 (Italian Pharma), PDF417, Micro PDF417, Composite Codes, Aztec, DataMatrix, MaxiCode, QR Code, Micro QR, Postal Codes<br>Refer to Product Reference Guide for complete list of symbologies. | <i>DS9808LR and DS9808LL** Laser Scanner Mode</i>                |  |
| PDF417 (and variants):              | PDF417 (Standard, Macro), MicroPDF417 (Standard, Macro), Composite Codes (CC-A, CC-B, CC-C)   | Light Source   | 650nm LED  |
| 2D                                  | TLC-39, Aztec (Standard, Inverse), MaxiCode, DataMatrix/ECC 200 (Standard, Inverse), QR Code (Standard, Inverse, Micro)   | Scan Angle   | 40° ±3° nominal  |
| Postal                              | U.S. Postnet and Planet, U.K. Post, Japan Post, Australian Post, Netherlands KIX Code, Royal Mail 4 State Customer, UPU FICS 4 State Postal, USPS 4CB, Canadian Post (Postbar)  | <b>** Available in the US only.</b>                              |  |
| Nominal Working Range (Handheld):   | See chart on back   | <b>RFID</b>  |  |
| Nominal Working Range (Hands-free): | See chart on back   | Frequency  | 902 - 928 MHz:<br>U.S., Canada, Mexico, Columbia, El Salvador, Guatemala<br><br>865.6 - 867.6 MHz:<br>Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Liechtenstein, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovak Republic, Slovenia, Spain, Sweden, Switzerland, United Kingdom,<br><br>902 - 907.5 MHz / 915 - 928 MHz:<br>Brazil<br><br>865 - 868 MHz / 920 - 925 MHz:<br>Hong Kong, Singapore<br><br>Other countries are pending.<br>Please contact your local Zebra sales representative for availability in your region. |
| Minimum Resolution                  | Code 39 – 4 mil, UPC – 7.8 mil (60%),<br>PDF417 – 5 mil, Datamatrix – 5 mil   | Tag Type   | EPCglobal Class 1 Gen 2 (ISO   |

### Integrated compact base

Requires very little real estate, enabling easy deployment in even the most space constrained cash wraps

## IMAGING CHARACTERISTICS

18000-6C)

**Graphics Format Support** Images can be exported as Bitmap, JPEG or TIFF

**Read Range/RF Power** Adjustable from near contact up to 40 inches/1 m depending on tag sensitivity and orientation

**Image Transfer Speed** USB 2.0: Up to 12 Megabits/second  
RS-232: Up to 115 kb/second

**Image Transfer Time** Typical USB application is ~0.2 seconds with a compressed JPEG of 100kb

**Image Quality** 120 DPI on a 4 x 6 in./10.2 x 15.2 cm document @ 6.5 in./16.5 cm

## INTERFACES

**Interfaces Supported** USB, RS-232, RS-485\* (Port 9B, Port 5B)  
(\*Tag "write" commands are not supported via RS-485)

## WARRANTY

Subject to the terms of Zebra's hardware warranty statement, the DS9808 is warranted against defects in workmanship and materials for a period of 3 years from the date of shipment. For the complete Zebra hardware product warranty statement, go to: <http://www.zebra.com/warranty>

## PRODUCT AVAILABILITY

Currently available in Austria, Belgium, Brazil, Bulgaria, Canada, Colombia, Cyprus, Czech Republic, Denmark, El Salvador, Estonia, Finland, France, Germany, Greece, Guatemala, Hong Kong, Hungary, Iceland, Ireland, Italy, Latvia, Liechtenstein, Lithuania, Luxembourg, Malta, Mexico, Netherlands, Norway, Poland, Portugal, Romania, Singapore, Slovak Republic, Slovenia, Spain, Sweden, Switzerland, United Kingdom, United States. Other countries are pending. Please contact your local Zebra representative for availability in your region.

## NOMINAL WORKING RANGE (HANDS-FREE):

DS9808-SR, DS9808-LR, DS9808-DL\*\* and DS9808-LL\*\*

**Code 39 – 5 mil:** 0 – 4.5 in. (0 – 11.4 cm)

**UPC/EAN – 10 mil (80%):** 0 – 7.0 in. (0 – 17.8 cm)

**UPC/EAN – 13 mil (100%):** 0 – 8.0 in. (0 – 20.3 cm)

**PDF417 – 6.6 mil:** 0 – 4.5 in. (0 – 11.4 cm)

**Datamatrix – 10 mil:** 0 – 4.5 in. (0 – 11.4 cm)

\*\* Available in the US only.

## USER ENVIRONMENT

**Operating Temp.** 32° to 104° F / 0° to 40° C

**Humidity** 5% to 95% RH (Non-Condensing)

**Drop Specification** Withstands multiple 4 ft./1.2 m drops to concrete

**Ambient Light Immunity** Incandescent – 150 ft. candles (1,600 Lux)  
Sunlight – 8,000 ft. candles (86,000 Lux)  
Fluorescent – 150 ft. candles (1,600 Lux)  
Mercury Vapor – 150 ft. candles (1,600 Lux)  
Sodium Vapor – 150 ft. candles (1,600 Lux)  
Immune to normal or artificial light

## REGULATORY

**Electrical Safety** UL60950-1; CSA C22.2 No. 60950-1; IEC60950-1

**Laser Safety** IEC 60825-1; 21CFR1040.10; CDRH Class II; IEC Class 2

**EMI/RFI** FCC Part 15 Class B; Canada RSS-210; ICES-003 Class B

**RF Exposure** FCC 47CFR Part 2, OET Bulletin 65 Supplement C

**Environmental** Compliant with RoHS directive 2002/95/EEC

**Regulatory Model Numbers** DS9808-RUS – US Version  
DS9808-RWW – Worldwide (Non-US) version

## RECOMMENDED SERVICES

**Customer Services** Service from the Start Advance Exchange Support

## NOMINAL WORKING RANGE (HANDHELD):

DS9808-LR and DS9808-LL\*\*

**Code 39 – 5 mil:** 0 – 5.0 in. (0 – 12.7 cm)

**UPC/EAN – 10 mil (80%):** 0 – 13.5 in. (0 – 34.3 cm)

**UPC/EAN – 13 mil (100%):** 0 – 18 in. (0 – 45.7 cm)

DS9808-SR and DS9808-DL\*\*

|   |                            |
|---|----------------------------|
| Code 39 – 5 mil:                                  | 0 – 4.5 in. (0 – 11.4 cm)  |
| UPC/EAN – 10 mil (80%):                           | 0 – 8.5 in. (0 – 21.6 cm)  |
| UPC/EAN – 13 mil (100%):                          | 0 – 10.5 in. (0 – 26.7 cm) |
| DS9808-SR, DS9808-LR, DS9808-DL** and DS9808-DL** |                            |
| PDF417 – 6.6 mil:                                 | 0 – 5.0 in. (0 – 12.7 cm)  |
| Datamatrix – 10 mil:                              | 0 – 6.0 in. (0 – 15.2 cm)  |

\*\* Available in the US only.

## ONE MULTI-FUNCTION SCANNER...MANY USES

The DS9808-R can be utilized in many different industries and many different applications, including:

### RETAIL

- Scanning items for purchase at the POS
- Beyond POS: Price checking, new inventory commission, separated inventory identification (e.g. fitting rooms), and returns processing
- RFID serialization protects against return attempts on items that were not purchased as well as items that were purchased at competing chains
- Commission RFID tags at point of manufacture or for stocking in store-level deployments
- Back-room price checking
- Return To Vendor (RTV) applications (old, damaged, mismatched product going back for credit)

### ASSET MANAGEMENT

- Commissioning assets into an RFID Asset Management application

### HOSPITALITY/LOYALTY

- Membership Identification

### GOVERNMENT/TRANSPORTATION

- Proof of Identity

### HEALTHCARE

- Medication check-in, receiving or dispensation

### PHARMACIES

- Check-in, receiving or dispensation at bottom-level, box level or item level RFID-tagged drugs and medication

### LIBRARIES

- Check-in, self checkout and auto-sorting

### LAW, INSURANCE AND GENERAL OFFICE ENVIRONMENTS:

#### ENTERPRISE FILE/DOCUMENT TRACKING

Real-time tracking of files and folders on desks and in boxes, containers, or reusable totes

- Cost-effective archiving and timely access/inquiries
- Compliance with regulatory requirements
- Automate monitoring of check-out time limitations and delinquent returns
- Automated alerts for unauthorized access



**ZEBRA**

